



標準材質: SUS304

金網標準メッシュ: 40メッシュ

SIZE		φD1				φD2	φD3	L	T	W	V	t	パンチング		
		JIS		ANSI/JPI									φ	P	t1
		10K	20K	150Lb	300Lb										
50A	2"	101	101	101.5	108	46	25	60	2	20	65	1.5	6	8	0.8
65A	2-1/2"	121	121	120.5	127	58	30	70	2	20	65	1.5	6	8	0.8
80A	3"	131	137	133.5	146.5	70	40	80	2	20	75	1.5	6	8	0.8
100A	4"	156	162	171.5	178	92	55	100	2	25	85	1.5	6	8	0.8
125A	5"	187	200	194	213	115	70	120	3	25	85	1.5	12	15	1.5
150A	6"	217	235	219.5	248	135	90	140	3	25	95	1.5	12	15	1.5
200A	8"	267	280	276.5	305	185	100	190	3	25	95	1.5	12	15	1.5
250A	10"	330	353	337	358.5	230	120	230	4	30	110	2.0	12	15	2.0
300A	12"	375	403	407	419	270	140	270	4	30	130	2.0	12	15	2.0
350A	14"	420	447	447	482.5	305	160	310	4	30	130	2.0	12	15	2.0
400A	16"	483	507	510.5	536.5	350	180	350	4	30	135	2.0	12	15	2.0
450A	18"	538	572	546	593.5	400	200	410	6	40	150	3.0	12	15	2.0
500A	20"	593	627	603	651	450	220	460	6	40	150	3.0	12	15	2.0